

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (cancelled)

2. (currently amended): The box of claim 4 38 wherein one of the test cap and the bottom wall has at least one tab that is insertable through a notch in the other of the test cap and the bottom wall for engagement with the other of the test cap and the bottom wall upon turning the test cap in the tightening direction to secure the test cap in place.

3. (original): The box of claim 2 wherein the other of the test cap and the bottom wall has a ramp that is engageable by the tab during turning of the test cap in the tightening direction to force the test cap into sealing engagement with the bottom wall radially outwardly of the notch.

4. (original): The box of claim 3 further comprising means for forming a fluid seal between the test cap and the bottom wall radially outwardly of the notch during turning of the test cap in the tightening direction.

5. (currently amended): The box of claim 4 38 further comprising a handle on the test cap to facilitate turning of the test cap in the tightening and untightening directions.

6. (original): The box of claim 5 wherein the handle includes spoke-like finger engaging portions for ease of turning the test cap in the tightening and untightening directions.

7. (currently amended): The box of claim 4 44 further comprising at least one locking tab on one of the bottom wall and the valve mount inserts and a notch in the other of the bottom wall and the valve mount inserts through which the locking tab is insertable for engagement with the other of the bottom wall and the valve mount inserts upon turning the valve mount inserts in a locking direction.

8. (original): The box of claim 7 further comprising a recess in the other of the bottom wall and the valve mount inserts in circumferential spaced relation from each notch for capturing the locking tab during turning of the valve mount inserts in the locking direction, and a ramp leading into each recess when each of the valve mount inserts is turned in the locking direction.

9. (original): The box of claim 7 wherein one of the test cap and the bottom wall has at least one tab that is insertable through a notch in the other of the test cap and the

bottom wall for engagement with the other of the test cap and the bottom wall upon turning the test cap in the tightening direction.

10. (cancelled)

11. (currently amended): The box of claim 4 37 wherein the two valve mount inserts are each insertable in any two of at least three openings, and a drain pipe is connectable to the third opening in which the two valve mount inserts are not inserted.

12. (original): The box of claim 11 wherein tail pieces surround each of the three openings in the bottom wall of the box.

13. (original): The box of claim 11 wherein one of the openings is located between the other two openings whereby the one opening is a center opening and the other two openings are right and left hand openings, respectively, the two valve mount inserts are insertable into any two of the openings, and a drain pipe is connectable to the third opening for establishing any one of a center drain arrangement, a right hand drain arrangement or a left hand drain arrangement.

14. -25. (cancelled)

26. (currently amended): The box of claim 25 38 wherein a single lever operated hot and cold water shut off valve assembly is mounted on the two joined valve mount inserts.

27. (currently amended): The box of claim 25 38 wherein individually operated hot and cold water shut off valves are mounted on the two joined valve mount inserts.

28. (currently amended): The box of claim 25 38 wherein the two joined valve mount inserts are connected together by a flange that overlies the center opening and the one of the two other openings in which the two joined valve mount inserts are inserted as a unit.

29. (original): The box of claim 28 further comprising means for establishing a fluid seal between the flange and the bottom wall of the box completely surrounding the center opening and the one of the two other openings in which the two joined valve mount inserts are inserted.

30. (currently amended): The box of claim 25 38 wherein a drain pipe is connectable to the other of the two other openings in which neither of the two joined valve mount inserts is inserted.

31. (currently amended): The box of claim 25 38 further comprising a snap lock connection between the two joined valve mount inserts and an edge of the openings in which the two joined valve mount inserts are inserted.

32. (currently amended): The box of claim 25 38 further comprising a solvent weld or adhesive connection between the flange of the two joined valve mount inserts and the bottom wall of the box.

33. (currently amended): The box of claim 25 38 further comprising at least one tail piece on the bottom wall of the box surrounding the opening in which neither of the two joined valve mount inserts is inserted for connecting a drain pipe thereto.

34. - 36. (cancelled)

37. (new - allowable claim 10 rewritten): A washing machine outlet box comprising a housing having a bottom wall containing multiple openings, two valve mount inserts selectively insertable into at least one of the openings to provide valve mounts for hot and cold water shut off valves, and a test cap that is insertable into an other of the openings, the test cap including means for sealing off the other opening during turning of the test cap in a tightening direction after inserting the test cap into the other opening, and being turnable in an untightening direction for removal of the test cap from the other opening, at least one locking tab on one of the bottom wall and the valve mount inserts and a notch in the other of the bottom wall and the valve mount

inserts through which the locking tab is insertable for engagement with the other of the bottom wall and the valve mount inserts upon turning the valve mount inserts in a locking direction, wherein one of the test cap and the bottom wall has at least one tab that is insertable through a notch in the other of the test cap and the bottom wall for engagement with the other of the test cap and the bottom wall upon turning the test cap in the tightening direction, and a recess in the other of the test cap and the bottom wall in circumferential spaced relation from each notch for capturing the locking tab during turning of each of the valve mount inserts in the locking direction, a first ramp leading into each recess when each of the valve mount inserts is turned in the locking direction, and a second ramp leading in the opposite direction from the notch that is engageable by the tab during turning of the test cap in the tightening direction to cause a seal on the test cap to press into sealing engagement with the bottom wall radially outwardly of the notch.

38. (new - allowable claim 14 rewritten): A washing machine outlet box comprising a housing having a bottom wall containing multiple openings, two valve mount inserts selectively insertable into at least one of the openings to provide valve mounts for hot and cold water shut off valves, and a test cap that is insertable into an other of the openings, the test cap including means for sealing off the other opening during turning of the test cap in a tightening direction after inserting the test cap into the other opening, and being turnable in an untightening direction for removal of the test cap from the other opening, wherein one of the openings is located equidistant between two other openings whereby the one opening is a center opening and the two other

openings are right and left hand openings, respectively, and the two valve mount inserts are joined together in spaced relation a distance corresponding to the spacing between the center opening and the other two openings, whereby the two joined valve mount inserts are insertable in the center opening and either one of the two other openings as a unit, and a drain pipe is connectable to the other of the two other openings in which neither of the joined valve mount inserts is inserted for establishing either a right hand drain arrangement or a left hand drain arrangement.

39. (new - allowable claim 15 rewritten): The box of claim 38 wherein a single lever operated hot and cold water shut off valve assembly is mounted on the two joined valve mount inserts.

40. (new - allowable claim 16 rewritten): The box of claim 38 wherein individually operated hot and cold water shut off valves are mounted on the two joined valve mount inserts.

41. (new - allowable claim 17 rewritten): The box of claim 38 wherein the two joined valve mount inserts are connected together by a flange that overties the center opening and the one of the two other openings in which the two valve mount inserts are inserted.

42. (new - allowable claim 18 rewritten): The box of claim 41 further comprising means for establishing a fluid seal between the flange and the bottom wall of the box

completely surrounding the center opening and the one of the two other openings in which the two joined valve mount inserts are inserted.

43. (new - allowable claim 19 rewritten): The box of claim 41 further comprising a solvent weld or adhesive connection between the flange of the two joined valve mount inserts and the bottom wall of the box.

44. (new - allowable claim 21 rewritten): A washing machine outlet box comprising a housing having a bottom wall containing multiple openings, two valve mount inserts selectively insertable into at least one of the openings to provide valve mounts for hot and cold water shut off valves, and a test cap that is insertable into an other of the openings, the test cap including means for sealing off the other opening during turning of the test cap in a tightening direction after inserting the test cap into the other opening, and being turnable in an untightening direction for removal of the test cap from the other opening, wherein the housing has a top wall containing at least one opening to allow the box to be mounted upside down with the bottom wall at the top and the top wall at the bottom for top mounting of the two valve mount inserts inside the box and for connecting a drain pipe to the opening in the top wall instead of to the other opening in the bottom wall in which neither of the two valve mount inserts is inserted.

45. (new - allowable claim 22 rewritten): The box of claim 44 further comprising a removable knockout covering the opening in the top wall.

46. (new - allowable claim 23 rewritten): The box of claim 44 further comprising a tail piece surrounding the opening in the top wall.

47. (new - allowable claim 34 rewritten): A washing machine outlet box comprising a housing having a bottom wall containing at least three openings, one of the openings being located equidistant between the two other openings whereby the one opening is a center opening and the two other openings are right and left hand openings, respectively, two valve mount inserts joined together in spaced relation, the spacing between the two joined valve mount inserts being such that the two joined valve mount inserts are insertable into the center opening and either one of the two other openings as a unit to provide valve mounts for hot and cold water shut off valves, wherein the housing has a top wall containing at least one opening to allow the box to be mounted upside down with the bottom wall at the top and the top wall at the bottom for top mounting of the two joined valve mount inserts inside the box and for connecting a drain pipe to the opening in the top wall instead of to the opening in the bottom wall in which neither of the two joined valve mount inserts is inserted.

48. (new - allowable claim 35 rewritten): The box of claim 47 further comprising a removable knockout covering the opening in the top wall.

49. (new - allowable claim 36 rewritten): The box of claim 47 further comprising a tail piece surrounding the opening in the top wall.